

## ***RIDEMAX IT 696 - Technical Specifications***



### *Description*

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

### *UM*

International Standard

### *Construction*

RADIAL

### *Machinery*

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/80 R 34 (18.4 R 34)
LI/SS	164 A8/159 D

### *Dimensions International Standard*

Section Width (mm)	479
Overall Diameter (mm)	1632
Static Loaded Radius (mm)	728
Rolling Circumference (mm)	4894
Rim Rec	W 15 L
Rim Alt	W 16 L
ECE	E4-106R-002296

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	2055	2540	2975	3455	3895	4375
50	2210	2725	3195	3715	4185	4700
40	2350	2900	3400	3950	4450	5000
30	2445	3015	3535	4110	4630	5200

Printed on 23/11/2020 08:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..