

AGRIMAX RT 945 - Technical Specifications



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer, Tractor

Version	STANDARD
Type	TL
Tyre Size	320/90 R 54 (12.4 R 54)
LI/SS	156 A8/B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1948
Static Loaded Radius (mm)	930
Rolling Circumference (mm)	6021
Rim Rec	W 10
Rim Alt	W 9; W 11
ECE	E11-106R-003474
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	4.8
50	1500	1935	2340	2595	2740	2995	3250	3470	3650	4000	-
40	1500	1935	2340	2595	2740	2955	3250	3470	3650	4000	-
30	1605	2075	2505	2780	2935	3210	3480	3715	3910	4280	-
10	-	1860	2340	2880	3420	3960	4080	4560	5040	5520	6000

Printed on 23/11/2020 08:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..