

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	300/80 R 24 (11.2 R 24)
LI/SS	133 A8/128 D

Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	501
Rolling Circumference (mm)	3296
Rim Rec	DW 10
ECE	E4-106R-002292

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	845	1045	1225	1420	1600	1800
50	910	1125	1320	1535	1725	1940
40	970	1195	1400	1625	1835	2060
30	1010	1245	1460	1700	1915	2150

Printed on 23/11/2020 14:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..