

## TF 9090 - Technical Specifications



**Description** TF 9090 is a tire designed for small tractors in soil tillage

operations. The special tread design provides excellent

steering performance on loose soil.

UM International Standard

Construction BIAS

Machinery Agriculture: Small Tractor

Industrial: Trailer

| Version   | STANDARD  |
|-----------|-----------|
| Туре      | π         |
| Tyre Size | 6.50 - 16 |
| LI/SS     | 91 A6     |

## **Dimensions International Standard**

| Ply Rating                 | 6                           |
|----------------------------|-----------------------------|
| Section Width (mm)         | 180                         |
| Overall Diameter (mm)      | 765                         |
| Static Loaded Radius (mm)  | 359                         |
| Rolling Circumference (mm) | 2280                        |
| Rim Rec                    | 4.50 E                      |
| Rim Alt                    | 4.00 E; 5 K; 5.00 F; 5.50 F |
| ECE                        | E4-106R-001960              |
| TRA Code                   | F2                          |

## Load capacity (Kg)

| km/h / bar | 3.10 |
|------------|------|
| 30         | 615  |

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..