

MP 570 - Technical Specifications



Description MP 570 is an agro-industrial tire, which is suitable for excavators and backhoe loaders. This tire provides good

traction and durability, as well as excellent self-cleaning

properties in all operating conditions.

UM International Standard

Construction BIAS

Machinery Agriculture: Backhoe Loader

Industrial: Backhoe Loader, Excavator, Universal Vehicle

Version STANDARD

Type TL

Tyre Size 14.5-20

Dimensions International Standard

Ply Rating	12
Section Width (mm)	360
Overall Diameter (mm)	1116
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3325
Rim Rec	11
Rim Alt	12 SDC

Load capacity (Kg)

km/h / bar	3.00
65	2430
50	2500

Printed on 24/11/2020 09:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

	-			