

## AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and

increased grip, is suitable for field trailers and

telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures

a longer tire life.

UM International Standard

Construction BIAS

Machinery Agriculture: Telehandler, Field Trailer

Industrial: Telehandler

Version STANDARD

Type TL

Tyre Size 27 X 10 - 15.3

## **Dimensions International Standard**

Ply Rating	8
Section Width (mm)	260
Overall Diameter (mm)	695
Static Loaded Radius (mm)	317
Rolling Circumference (mm)	2071
Rim Rec	9.00
ECE	E4-106R-002324

## Load capacity (Kg)

km/h / bar	3.10
10 FR	1365
25 FR	1160
30 FR	1090
40 FR	975
10 DW	965
25 DW	820
30 DW	775
40 DW	690

Printed on 24/11/2020 09:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..