

AW 705 - Technical Specifications



Description	AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.
UM	International Standard
Construction	BIAS
Machinery	Agriculture: Baler, Implement Machinery, Trailer

Version	STANDARD
Type	TT
Tyre Size	16.0/70 - 20

Dimensions International Standard

Ply Rating	14
Section Width (mm)	408
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3155
Rim Rec	13.0
Rim Alt	12 SDC; 13 SDC; 14
ECE	E4-106R-003368

Load capacity (Kg)

km/h / bar	
	3.50
10 FR	5250
25 FR	4465
30 FR	4200
40 FR	3750

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..