

LG RIB - Technical Specifications



Description LG RIB is a lawn and garden tire suitable for mowers and

small tractors. Its tread pattern has been designed for making the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG RIB is available in an "aramid-belted" version for users

who need strengthened puncture resistance.

UM International Standard

Construction BIAS

Machinery Agriculture: Mower, Small Tractor

Version STANDARD

Type TL

Tyre Size 16 X 6.50 - 8

Dimensions International Standard

Ply Rating	4	
Section Width (mm)	170	
Overall Diameter (mm)	408	
Static Loaded Radius (mm)	182	
Rolling Circumference (mm)	1183	
Rim Rec	5.3751-55;1-70;1-90	
ECE	E11-106R-003467	

Load capacity (Kg)

km/h / bar	1.90
15	280

Printed on 25/11/2020 08:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..