

## LG 408 - Technical Specifications



**Description** LG 408 is a lawn and garden tire suitable for mowers and

small tractors. The specific tread pattern makes the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG 408 is available in an "aramid-belted" version for users who need

strengthened puncture resistance.

UM International Standard

Construction BIAS

Machinery Agriculture: Mower, Small Tractor

Version STANDARD

Type TL

Tyre Size 24 X 13.00 - 12

## **Dimensions International Standard**

Ply Rating	6	
Section Width (mm)	320	
Overall Diameter (mm)	605	
Static Loaded Radius (mm)	269	
Rolling Circumference (mm)	1755	
Rim Rec	10.5   - 55 ;   - 70 ;   - 90	
ECE	E11-106R-003464	

## Load capacity (Kg)

km/h / bar	2.20
15	1085

Printed on 24/11/2020 14:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..