

## MP 585 - Technical Specifications



### Description

MP 585 is an agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a block pattern that offers maximum stability and durability in the most difficult working conditions, also at high speeds.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Universal Vehicle  
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	12.5 - 20

### Dimensions International Standard

Ply Rating	12
Section Width (mm)	335
Overall Diameter (mm)	1050
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3130
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022635

### Load capacity (Kg)

km/h / bar	
90	3.50
50	2000
	2240

*its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*