

FL 630 ULTRA - Technical Specifications



Description FL 630 ULTRA is suitable for trailers, tankers and

spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for

multipurpose use on any kind of land or on the road. FL

630 ULTRA stands for extraordinarily reduced soil

compaction.

UM International Standard

Construction RADIAL

Machinery Agriculture: Spreader, Tanker, Trailer

Version STANDARD

Type TL

Tyre Size 560/60 R 22.5

LI/SS 161 D/172 A8

Dimensions International Standard

Section Width (mm) 543

Overall Diameter (mm) 1244

Static Loaded Radius (mm) 535

Rolling Circumference (mm) 3760

Rim Rec AG 16.00

Rim Alt 16.00; 17.00; AG 20.00

ECE E11-106R-003013

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1350	1540	1730	2150	2445	2825	3200	3495	3835	4210
65	1480	1690	1900	2360	2685	3100	3515	3840	4210	4625
50	1795	2050	2300	2860	3250	3755	4260	4650	5100	5600
40	2020	2305	2585	3215	3655	4225	4790	5230	5735	6300
30	2240	2555	2865	3565	4055	4680	5310	5800	6360	6985
25	2340	2670	3000	3730	4240	4900	5560	6070	6655	7310
10	2665	3040	3415	4250	4830	5580	6330	6910	7580	8325

Printed on 25/11/2020 14:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..