

## SKID POWER HD - Technical Specifications



**Description** SKID POWER HD has been designed for skid steers in

construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD is the ideal tire for loose surfaces and heavy-duty

service.

UM International Standard

Construction BIAS

Machinery Industrial: Skid Steer

Version STANDARD

Type TL

Tyre Size 18 X 8.5 - 10

## **Dimensions International Standard**

Ply Rating	8
Section Width (mm)	205
Overall Diameter (mm)	465
Static Loaded Radius (mm)	213
Rolling Circumference (mm)	1372
Rim Rec	7.00   - 55 ;   - 70 ;   - 90

## Load capacity (Kg)

km/h / bar	3.00
10	720
15	570
25	525

Printed on 25/11/2020 15:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

