

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Sprayer, Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/85 R 20 (12.4 R 20)
LI/SS	119 A8/B

### Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1052
Static Loaded Radius (mm)	467
Rolling Circumference (mm)	3100
Rim Rec	W 11
Rim Alt	W 9; W 10
ECE	E4-106R-000645
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	750	875	995	1120	1240	1360
40	750	875	995	1120	1240	1360
30	805	935	1070	1200	1330	1460
10 LT	1005	1170	1335	1500	1665	1825
10 HT	805	935	1070	1200	1330	1460

Printed on 26/11/2020 08:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..