

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/65 R 28
LI/SS	142 D/145 A8

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1335
Static Loaded Radius (mm)	610
Rolling Circumference (mm)	4091
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E4-106R-000653
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1275	1485	1670	1855	2045	2200	2440	2650
50	1340	1560	1755	1950	2145	2315	2565	2785
40	1395	1625	1830	2030	2235	2410	2670	2900
30	1465	1710	1925	2135	2350	2535	2810	3050
10 LT	1710	1995	2240	2490	2740	2955	3275	3555
10 HT	1465	1710	1925	2135	2350	2535	2810	3050

Printed on 26/11/2020 08:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..