

## AS 507 - Technical Specifications



**Description**

AS 507 is suitable for soil tillage with trailers and implement machinery. It features excellent self-cleaning properties and increased traction on the ground.

**UM**

International Standard

**Construction**

BIAS

**Machinery**

Agriculture: Implement Machinery, Trailer

Version	STANDARD
Type	TL
Tyre Size	185/65 - 15

### Dimensions International Standard

Ply Rating	4
Section Width (mm)	185
Overall Diameter (mm)	640
Static Loaded Radius (mm)	301
Rolling Circumference (mm)	1894
Rim Rec	5.5

### Load capacity (Kg)

km/h / bar	2.80
10 FR	810
25 FR	690
30 FR	650
40 FR	580
10 DW	560
25 DW	475
30 DW	450
40 DW	400

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*