

AW 909 - Technical Specifications



| | |
|---------------------|---|
| Description | AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road. |
| UM | International Standard |
| Construction | BIAS |
| Machinery | Agriculture: Baler, Implement Machinery, Trailer |

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 11.5/80 - 15.3 |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 10 |
| Section Width (mm) | 297 |
| Overall Diameter (mm) | 844 |
| Static Loaded Radius (mm) | 370 |
| Rolling Circumference (mm) | 2473 |
| Rim Rec | 9.00 |
| ECE | E4-106R-001893 |

Load capacity (Kg)

| km/h / bar | |
|------------|------|
| | 3.40 |
| 10 FR | 2730 |
| 25 FR | 2320 |
| 30 FR | 2185 |
| 40 FR | 1950 |

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..