

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer, Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/95 R 16 (7.50 R 16)
LI/SS	106 A8/B

Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	806
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2415
Rim Rec	W 7
Rim Alt	W 6 ; 6 LB
ECE	E4-106R-000608
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	450	515	590	665	745	820	885	950
40	450	515	590	665	745	820	885	950
30	480	555	635	715	800	880	950	1020
10 LT	600	690	795	895	995	1100	1190	1275
10 HT	480	555	635	715	800	880	950	1020

Printed on 19/11/2020 08:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..