

SM 68 (GK) - Technical Specifications



Description

SM 68 has been specially designed for go karts. Its smooth tread design provides excellent performance in sport activities. Shore A hardness 68.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Go-Kart

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 10 X 4.5 - 5 |

Dimensions International Standard

| | |
|-----------------------|-----|
| Section Width (mm) | 130 |
| Overall Diameter (mm) | 260 |
| Rim Rec | 4.5 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 4.00 |
| - | 130 |

Printed on 19/11/2020 09:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..