

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tractor, Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/65 R 18
LI/SS	113 A8/B

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	899
Static Loaded Radius (mm)	400
Rolling Circumference (mm)	2667
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E4-106R-001816
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	645	760	865	970	1060	1150
40	645	760	865	970	1060	1150
30	695	820	930	1040	1140	1235
10 LT	870	1020	1160	1300	1425	1545
10 HT	695	820	930	1040	1140	1235

Printed on 19/11/2020 15:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..