

## MULTIMAX MP 540 - Technical Specifications



### Description

MULTIMAX MP 540 has been designed by BKT for multi-purpose vehicles in municipality/maintenance applications. It is suitable for all universal vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads at high speeds. In addition, its block pattern design provides outstanding stability and durability.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Universal Vehicle  
Industrial: Universal Vehicle

Version	STANDARD
Type	TL
Tyre Size	335/80 R 20
LI/SS	149 K

### Dimensions International Standard

Section Width (mm)	340
Overall Diameter (mm)	1044
Static Loaded Radius (mm)	492
Rolling Circumference (mm)	3258
Rim Rec	11
Rim Alt	-
ECE	E11-54R-0015909

## Load capacity (Kg)

km/h / bar	4.0	4.5	5.0	5.5	6.0	6.5
110	2205	2420	2635	2845	3050	3250
100	2205	2420	2635	2845	3050	3250
90	2250	2470	2685	2900	3110	3315
80	2290	2520	2740	2955	3170	3380
70	2360	2595	2820	3045	3265	3480

Printed on 20/11/2020 08:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..