

## TR 678 - Technical Specifications



**Description** TR 678 has been specially designed for forestry applications. Its robust lug design provides excellent

traction and self-cleaning. The strong casing structure stands for high load capacity whereas its steel belts protect the tire from punctures and damages. TR 678 features a cut-resistant tread compound providing excellent cut-and-chip resistance even on difficult terrains

under extreme conditions.

UM International Standard

Construction BIAS

Machinery Agriculture: Implement Machinery, Trailer

Industrial: Excavator, Trailer

Version STEEL BELTED

Type TL

*Tyre Size* 600/65 - 34

LI/SS 164 A2/160 A6

## **Dimensions International Standard**

Ply Rating	14
Section Width (mm)	610
Overall Diameter (mm)	1644
Static Loaded Radius (mm)	758
Rolling Circumference (mm)	4916
Rim Rec	DW 20 B
ECE	E11-106R-003648
TRA Code	LS2

## Load capacity (Kg)

km/h / bar	2.40
30	4500
10	5000

## Printed on 20/11/2020 15:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..