

LG 306 - Technical Specifications



Description	LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.
UM	US Standard
Construction	BIAS
Machinery	Agriculture: Mower, Small Tractor
Version	ARAMID BELTED
Туре	TL
Tyre Size	18 X 9.50 - 8

Dimensions US Standard

Usa code	94012770
Ply Rating	6
Section Width (inch)	9.1
Overall Diameter (inch)	18.5
Static Loaded Radius (inch)	8.1
Rolling Circumference (inch)	53.7
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003501

Load capacity (lbs)

mph / psi	36
10	1335

Printed on 24/11/2022 13:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

prior written consent by Balkrishna Industries Ltd..