

## LG 306 - Technical Specifications



**Description** LG 306 is a lawn and garden tire suitable for mowers. In

some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who

need strengthened puncture resistance.

UM US Standard

Construction BIAS

Machinery Agriculture: Mower, Small Tractor

Version STANDARD

Type TL

Tyre Size 33 X 15.50 - 16.5

## **Dimensions US Standard**

| Usa code                     | 94037100        |
|------------------------------|-----------------|
| Ply Rating                   | 10              |
| Section Width (inch)         | 15.6            |
| Overall Diameter (inch)      | 33.1            |
| Static Loaded Radius (inch)  | 14.7            |
| Rolling Circumference (inch) | 98.2            |
| Rim Rec                      | 12.00           |
| ECE                          | E11-106R-003004 |

## Load capacity (lbs)

| mph / psi | 30   |
|-----------|------|
| 10        | 3595 |

Printed on 01/12/2022 12:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without

